


* For mounting on concrete + metallic plate, please contact us.

CLIPS	C max	Tightening torque (Nm)			Est'd weight
		Bolt or screw grade			
	mm	4.6	5.6	8.8	kg
41/075/AN	28				0,580
41/075/BN	35	150	200	400	0,600
41/075/CN	40				0,630
Admissible side load (kN)		30	40	75	

N : nose height, not compressed, adapted to the rail type (see table overleaf).

SUB-PARTS




All parts are hot dip galvanized.

Full designation	
41/075/AN or 41/075/BN or 41/075/CN	
Components	
①	1x 41/075/R
②	1x 41/075/28/N or 41/075/35/N or 41/075/40/N

For further anti-corrosion coating : see leaflet "Patented boltable clips".

CLIP SELECTION FOR EACH RAIL

	F mm	K mm	H mm	Weight kg/m	Mounting	
					with	without
					pad	
A 65	175.0	65.0	75.0	43.10	41/075/BJ	41/075/AJ
A 75	200.0	75.0	85.0	56.20	41/075/BJ	41/075/AI
A 100	200.0	100.0	95.0	74.30	41/075/BI	41/075/AI
A 120	220.0	120.0	105.0	100.00	41/075/CJ	41/075/BM
A 150	220.0	150.0	150.0	150.30	41/075/CI	41/075/BJ
MRS 51 (104 CR)	127.0	63.5	127.0	51.59	41/075/CM	41/075/BM
MRS 52 (105 CR)	131.8	65.1	131.8	52.09	41/075/BI	41/075/AI
MRS 67 (135 CR)	131.8	76.2	146.0	66.97	41/075/CM	41/075/BM
MRS 85 (171 CR)	152.4	101.6	152.4	84.83	41/075/CI	41/075/BJ
MRS 87 A (PRI 85 R)	152.4	101.6	152.4	86.80	41/075/CI	41/075/BJ
MRS 87 B (175 CR)	152.4	102.4	152.4	86.80	41/075/CJ	41/075/BM
MR 151 (PR 7)	220.0	150.0	150.0	151.30	41/075/CI	41/075/BJ
Vign 36	115.0	58.2	128.0	36.54	41/075/BJ	41/075/AJ
Vign 46 (U 33)	134.0	62.0	145.0	46.36	41/075/BJ	41/075/AJ
Vign 50 (U 50)	140.0	65.0	153.0	50.88	41/075/BI	41/075/AI
Vign 52	150.0	65.0	150.0	52.34	41/075/BJ	41/075/AJ
Vign 55	134.0	62.0	155.0	56.07	41/075/CJ	41/075/BM
S 41/10	125.0	67.0	138.0	41.38	41/075/BJ	41/075/AJ
S 49	125.0	67.0	149.0	49.43	41/075/BI	41/075/AI
S 54	125.0	67.0	154.0	54.54	41/075/CM	41/075/BM
S 64	150.0	74.0	172.0	64.92	41/075/CM	41/075/BM
GX 40	127.0	63.5	127.0	39.80	41/075/BJ	41/075/AJ
GX 42	131.8	65.1	131.8	42.16	41/075/BJ	41/075/AJ
EB 50 T	140.0	72.0	151.0	50.10	41/075/BI	41/075/AI
UIC 54	140.0	70.0	159.0	54.43	41/075/BI	41/075/AI
UIC 60	150.0	72.0	172.0	60.34	41/075/BI	41/075/AI
56 CR	171.0	76.0	101.5	56.81	41/075/BI	41/075/AI
89 CR	178.0	102.0	114.0	89.81	41/075/CI	41/075/BJ
101 CR	165.0	100.0	155.0	100.38	41/075/CH	41/075/BI
BS 113 A	139.7	69.9	158.8	56.40	41/075/BI	41/075/AI
JIS 37	122.2	62.7	122.2	37.20	41/075/BJ	41/075/AJ
JIS 40 N	122.0	64.0	140.0	40.90	41/075/BJ	41/075/AJ
JIS 50 N	127.0	65.0	153.0	50.40	41/075/BI	41/075/AI
JIS 60	145.0	65.0	174.0	60.80	41/075/CM	41/075/BM
CR 73	140.0	100.0	135.0	73.30	41/075/CJ	41/075/BJ
CR 100	155.0	120.0	150.0	100.20	41/075/CH	41/075/BI
AS 41	127.0	63.5	137.0	40.72	41/075/BJ	41/075/AJ
AS 50	127.0	69.9	154.0	50.80	41/075/BI	41/075/AI
AS 60	146.0	69.9	170.0	60.99	41/075/BI	41/075/AI
AS 73 (MRS 73)	146.0	70.0	157.0	73.63	41/075/CH	41/075/BI
AS 86 (MRS 86)	165.0	102.0	102.0	85.60	41/075/CI	41/075/BJ

For rail sections other than those listed on this page, please contact us.

We reserve the right to discontinue or change specifications or design at any time without prior notice and without incurring any obligation whatsoever.


GANTREX GmbH

Hirzenrott 10 – D 52076 Aachen • Tel. +49 (0)2408 9454-0 • Fax +49 (0) 2408 9454-28

E-mail : info@de.gantry.com • http://www.gantrex.de